HOSPITAL FACILITY SERVICES INFO@HOSPITALFS.COM

OIL-LESS STRAIGHT PISTON AIR COMPRESSOR

PC2/50


ISO 9001-2008 Certified




ISO 13485-2008 Certified









- Specialty Niploid Coated cylinder and high temperature piston rings for Long Service Life
- 100% Duty Cycle, Runs continuously
- Ease of Maintenance
- ASME rated air tank, internally & externally coated to prevent corrosion
- Optional self regenerative dessicant air dryer
- Integrated Aftercooler
- 5 micron particle filters with autodrain
- Optional Silencing Cabinet 56 dB/A





HP	1.5
Output Free Air	6.35 CFM
Output Free Air	180 L. Min
Max Pressure PSI	116 PSI
Max Pressure Bar	8 bar
Max Current 115V	17 Amps
Max Current 220V	7 Amps



Please factor 20% air-flow reduction for 50hz applications

•

THE PC2 QUIET OIL LESS COMPRESSOR IS AVAILABLE IN MULTIPLE CONFIGURATIONS TO SUIT YOUR NEEDS. FOR A DETAILED VIEW OF DIFFERENT CONFIGURATIONS, PLEASE CONSULT PAGE TWO OF THIS BROCHURE.

PC2/50

OIL-LESS STRAIGHT PISTON AIR COMPRESSOR

PC 2/50/3 Compressor + Air Receiver

ITEM # M57090US - 115V/60 HZ ITEM # M57020US - 220V/60 HZ ITEM # M57010 - 220V/50 HZ

Noise Level 72 dB/A Tank Size 13gal(50L) Dimensions (in.) 25L x 18W x 29H

Weight 97 Lbs





PC 2/50/37D Compressor + Air Receiver + Dryer

ITEM # M57291 - 115V/60 HZ ITEM # M57220US - 220V/60 HZ ITEM # M57211 - 220V/50 HZ

 Noise Level
 72dB

 Tank Size
 13gal(50L)

 Dimensions (in.)
 25L x 22W x 29H

 Weight
 141 Lbs

PC2/50/379D Compressor + Air Receiver + Dryer + Silencing Cabinet

ITEM # M57490US - 115V/60 HZ ITEM # M57420 - 220V/60 HZ ITEM # M57411 - 220V/50 HZ

ITEM # M57411 - 220V/50 HZ ITEM # M57391 - 115V/60 HZ (WITH DRYER) ITEM # M57321 - 220V/60HZ (WITH DRYER) ITEM # M57311 - 220V/50HZ (WITH DRYER)

Noise Level 56 dB/A
Tank Size 13 gal (50L)
Dimensions (in.) 29L x 23W x 32H

Weight 207 lbs



*Silencing Cabinet cannot be purchased separately