MiniOX® 100 Oxygen Analyzer

The MiniOX 100 hand held oxygen analyzer is simple to use with one-touch calibration and a calibration reminder combined with a 2 year warranty, auto-off and a compact design. This analyzer is great for spot-checking O_2 percentage in hospitals, clinics and in homecare environments.

Part Numbers

MiniOX 100	600100
MiniOX 100 (International)	600101


Accessories

Tee Adapter (15 mm)	606901
Flow Diverter	606902
Barbed Adapter	606903





- 1 **LCD Display** Large, easy-to-read, liquid crystal display
- (2) **Calibration** New and improved one-touch calibration button
- ③ **ON/OFF Button** One-touch on and off
- (4) **Protective Wrap** Overmold for extra protection
- (5) Lanyard Attachment Small, convenient and portable



Specifications

Sensor Type	MiniOX 250 galvanic cell with temperature compensation (non-replaceable)
Measurement Range	0.0-99.9% Oxygen (gas)
Resolution/Display	0.1%, The three digit LCD indicates values between 0.0-99.9% Oxygen over range indicated by one decimal point on display located after first digit
Response Time	<15 Seconds for 90% step change (at 25° C)
Linearity / Accuracy	@15° to 40° C. \pm 1% of full scale at constant temperature, R.H. and pressure when calibrated at full scale \pm 3% actual Oxygen level over full operating temperature
Power	Powered by one internal, non-replaceable, Lithium battery, CR2450. Power on push button automatically shuts off after 80 seconds time-out. Electronics rated general purpose. Not for use in hazardous areas or for use with flammable gases.
Battery Life	Approximately 1850 hours (74,000 cycles)
Sample Port	M-16 x 1 thread with diverter fitting and barbed tubing adapter
Diverter Fitting	Fits medical standard 15mm "T" adapter
Temperature	Operating: 15° to 40° C, Storage: -15° to 50° C
Expected Storage Life	Two months. Special freshness seal on sensor.
Operating Pressure	Atmospheric pressure 3 psig
Environmental	General purpose housing equivalent to NEMA 1. MiniOX is not waterproof. 0-95% RH, non-condensing
Weight	Approximately 3 oz (85 grams)

C E 0123

© 2017 Ohio Medical, LLC. All rights reserved.

This document contains information that is proprietary and confidential to Ohio Medical, LLC. Use of this information is under license from Ohio Medical, LLC. Any use other than that authorized by Ohio Medical, LLC is prohibited.



Ohio Medical, MiniOX, and the Ohio Medical logo are registered trademarks of Ohio Medical, LLC. Maxtec is a trademark of Maxtec, LLC.

1111 Lakeside Drive | Gurnee, IL 60031-4099 | Phone: 1-866-549-6446 | Fax: 1-847-855-6300 | www.ohiomedical.com

www.ohiomedical.com 550657 (Rev. 1, 02/2017)