Regulator AM 250



1



General Specifications:

The Amico AM 250 Series Regulator shall be for a line supply of a single stage and medium duty type.

Application and Uses

Medium to high capacity Ideal for welding and cutting applications Compact, single stage construction

Design Construction

Forged brass body and housing cap 2" (5.1 cm) gauges Stem type seat mechanism 1-3/4" (4.4 cm) stainless steel diaphragm External self reseating relief valve Sintered inlet filter

Performance

Maximum Inlet - 3000 PSIG Maximum Delivery Range - 350 PSIG Flow - See charts


Specifications and Materials

Dimensions - 6-3/8" w x 5-1/8" h x 4-1/4" d (16.2 cm x 13.0 cm x 10.8 cm)

Weight - 2 lbs 15 oz (1.4 kg) Body - Forged brass Diaphragm - Fabric reinforced neoprene Housing cap - Forged brass Inlet filter - Bronze

Amico

Technical Specifications



Model Numbers

P-REG-L250-GAS

For proper model number replace "GAS" with the following:			
Oxygen	=	OXY	
Nitrous Oxide	=	N20	
Medical Air	=	AIR	
Carbon Dioxide	=	CO2	
Nitrogen	=	NIT	

Amico Corporation 85 Fulton Way, Richmond Hill, ON L4B 2N4, Canada I 71 East Industry Court, Deer Park , NY 11729, USA Toll Free Tel: 1.877.462.6426 | Toll Free Fax:1.866.440.4986 Tel: 905.764.0800 | Fax: 905.764.0862